



Item # _____

Job _____

HD SUPER™ WORK CENTER WITH OVERHEAD

- **Organize Work Areas:** HD Super™ Work Center with overhead structure helps organize work areas, keeping the work surface neat and clutter-free.
- **Saves Steps, Time:** Overhead accessories provide a place for spices, pots and pans and utensils, so they are always within easy reach.
- **Choice of Three Overhead Accessories:**
 - Cantilever Shelf** — 12" (305mm) wide wire shelf holds cooking utensils, ingredients, etc.
 - Spice Rack** — wire rack keeps spices handy.
 - Hook** — attaches to the edge of the other accessories to hold pots, pans, utensils, etc.
- **Arrange Accessories to Suit Needs:** The cantilever shelf and the spice rack can be placed at any level above the table top, and can be adjusted as needed in two-inch increments. They can be arranged in any combination and number along the 88" (2235mm) high HD Super™ back posts
- **Unique Sanitary Seal Around Back Posts:** The 88" (2235mm) high back posts extend up through holes in the table, which is embossed at $\frac{3}{8}$ " (12mm) around the holes. A seal at the top of the embossment creates a watertight seal between the posts and the table, preventing food particles and liquids from entering the holes.
- **Heavy-Duty:** HD Super™ Work Centers are designed and built for heavy-duty foodservice and food processing applications. The 34" (864mm) high work surface is made of seamless, 14-gauge stainless steel with a support structure that virtually eliminates any "drumming" effect.
- **Greater Rigidity:** Work Centers feature sturdy $1\frac{5}{8}$ " (38mm) diameter HD Super™ posts and the tapered sleeves and corners of patented Super Erecta Shelf® construction. These two features assure a rigid, wobble-free table.
- **Easy to Assemble:** Units are shipped knocked down and can be put together in minutes without special tools.
- **Several Styles Available:** HD Super™ Work Centers with overhead structure come in 12 models, all with stainless steel table tops, but offering a choice of chrome-plated or stainless steel posts and either a shelf or a three-sided frame which can be placed at the desired level below the top. (NSF requires that shelves be placed at least 6", 152.4mm above the floor.) Additional shelves can be ordered from HD Super™ stock



*Work Center with Cantilever Shelf
and Spice Rack Accessories*



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

Copyright © 1999 InterMetro Industries Corp.



Work Center with Overhead

17.26



WORK CENTER WITH OVERHEAD

Specifications:

• **Top:** Seamless 14-gauge T-304 stainless steel, embossed at $\frac{3}{8}$ " (12mm) around holes for posts, neoprene-sealed at top of embossment. 14-gauge (.075) channel support structure is nickel/chrome-plated after fabrication.

• **Bottom Shelf:** 16-gauge galvanized or T-304 stainless steel. 14-gauge available on special order. 30" x 60" (760 x 1525mm) work centers have 24" x 54" (610 x 1370mm) bottom shelves; 30" x 72" (760 x 1825mm) and 30" x 96" (760 x 2439mm) work centers have 24" x 60" (610 x 1525mm) bottom shelves.


• **Bottom Frame:** Three-sided tubular frame available in 16-gauge chrome-plated or stainless steel. 30" x 60" (760 x 1525mm) work centers have 24" x 54"

(610 x 1370mm) bottom frames; 30" x 72" (760 x 1825mm) and 30" x 96" (760 x 2439mm) work centers have 24" x 60" (610 x 1525mm) bottom frames.


• **Posts:** Steel posts have an outside diameter of $1\frac{5}{8}$ " (38mm), with rolled grooves in 2" (51mm) increments along entire height.

• **Shelf and Spice Rack:** Open wire construction, with tapered corners that fit over tapered split sleeves on $1\frac{5}{8}$ " (38mm) diameter HD Super™ posts. Available in stainless steel or chrome-plated.


• **Other Accessories:** See data sheet #17.22 for cutting board holder and drawers.



Cantilever Shelf



Spice Rack



Hook

Dimensions

Width		Length		Overall Height		Approx. Pkd. Wt.		Post Material	Bottom Shelf Material	Bottom Frame Material	Cat. No.
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)				
30	760	60	1525	88 $\frac{1}{4}$	2242	158	72	SS	SS	—	WTC306FS
30	760	72	1825	88 $\frac{1}{4}$	2242	182	83	SS	SS	—	WTC307FS
30	760	96	2439	88 $\frac{1}{4}$	2242	234	106	SS	SS	—	WTC309FS
30	760	60	1525	88 $\frac{1}{16}$	2237	160	73	Chrome	Galvanized	—	WTC306FC
30	760	72	1825	88 $\frac{1}{16}$	2237	184	83	Chrome	Galvanized	—	WTC307FC
30	760	96	2439	88 $\frac{1}{16}$	2237	236	107	Chrome	Galvanized	—	WTC309FC
30	760	60	1525	88 $\frac{1}{4}$	2242	137	62	SS	—	SS	WTC306US
30	760	72	1825	88 $\frac{1}{4}$	2242	160	73	SS	—	SS	WTC307US
30	760	96	2439	88 $\frac{1}{4}$	2242	212	96	SS	—	SS	WTC309US

LOAD RATING FOR OVERHEAD: 300 lbs. (136 Kg.) maximum.

LOAD RATING FOR TOP: 3060-625 lbs. (283 kg.); 3072-750 lbs. (340 kg.); 3096-1000 lbs. (454 kg.) equally distributed.

Accessories

Spice Rack

Fits Units	Inside Height		Inside Depth		Inside Length		Approx. Pkd. Wt.		Cat. No. Chrome-Plated	Cat. No. Stainless
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)		
60" (1525mm) long	1 $\frac{5}{16}$	49.2	4 $\frac{7}{8}$	111	51 $\frac{9}{16}$	1310	7.7	3.5	654SRC	654SRSS
72" (1825mm) long & 96" (2439mm) long	1 $\frac{5}{16}$	49.2	4 $\frac{7}{8}$	111	57 $\frac{9}{16}$	1462	8.3	3.75	660SRC	660SRSS

Cantilever Shelf

Fits Units	Width		Length		Approx. Pkd. Wt.		Cat. No. Chrome-Plated	Cat. No. Stainless
	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)		
60" (1525mm) long	12	43	54	1370	11.8	5.4	1254CHC	1254CHS
72" (1825mm) long & 96" (2439mm) long	12	43	60	1525	12.7	5.8	1260CHC	1260CHS

LOAD RATING: 150 lbs. (68 kg.) equally distributed.

Hook

(in.)	Width		(in.)	Depth		(in.)	Height		Approx. Pkd. Wt.	Cat. No. Chrome-Plated	Cat. No. Stainless
	(mm)	(mm)		(mm)	(mm)		(lbs.)	(kg)			
$\frac{3}{8}$	12	1 $\frac{11}{16}$	43	3 $\frac{7}{16}$	87	0.1	0.04	HK23C	HK23S		

Manufactured by:



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705
Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232
Visit Our Web Site: www.metro.com

L02-120
Rev. 9/00
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

