



PRODUCT NUMBER: 1032374

## Miller kernmantel edge shock absorbing lanyard 2 meters with a twist lock and a GO55 scaffold hook karabiner.

Miller kernmantel edge shock absorbing lanyard 2 meters with a steel twist lock karabiner and a GO55 steel scaffold hook.



### Overview

**Reference Number**

1032374

**Product Type**

Fall Protection

**Range**

Shock Absorbing Lanyards

**Line**

Cut resistant

**Brand**

Miller by Honeywell

**Industry**

- Building and Construction

**Product Use**

Fall arrest lanyards will allow the worker to fall but prevents him from hitting the next lower level, such as the ground, (if well attached). It includes a shock absorber that dissipates the forces exerted on the body in the case of a fall to stay below 6 KN.

This single lanyard is edge tested for safe working on edges ( $r \geq 0,5$  mm).

### Features & Benefits

**Feature**

New design : \* Lanyard manufactured with a light green rope with black stripes, which are highly visible from a distance increasing safety at work. \* The stitches are highly visible which facilitates the safety check before use.

**Benefit**

\* Lanyard edge tested : manufactured with high quality kernmantel rope and have special. \* The rope is 2 times more resistant to the abrasion than the other standard ropes.

## Technical Description

**Length**

2 M

**Weight**

1,040 KG

**Breaking Strength**

> 22 KN

**Operating Temperature**

-30°C to +50°C

### Rope

**Rope Raw Material**

Kernmantel Ø 11 mm polyester sheath and polyamide core

### Connector

**Connector Type**

Twist lock karabiner

**Connector Raw Material**

steel

**Connector Opening**

17 mm

**Connector Breaking Strength**

> 22 KN

**Connector Standard**

EN 362 : 2004

### Connector

**Connector Type**

GO55 scaffold hook

**Connector Raw Material**

steel

**Connector Opening**

55 mm

**Connector Breaking Strength**

> 25 KN

**Connector Standard**

EN 362 : 2004

### Energy Absorber

**Energy Absorber Raw Material**

Resistant webbing shock absorber with protective cover

## Certifications

**EU Category PPE**

3

**Quality Assurance**

ISO 9001 / 2000

**EU Certification**

EU Attestation

**Certifications**

- EN 355 / VG 11 PFE 11.074

**REACH****EU Regulation 1907/2006 (REACH) Compliance**

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

## Additional Information

### User Manual

NT90004208 IND L

### User Information Sheet

User manual

## Maintenance

### Life Cycle

Life expectancy of our lanyards is 10 years from the date of manufacture.

### Care Instructions

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.