



## Isopropyl Alcohol Fluid

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: Supacide 0.2 Filtered IPA Fluid

Part Number: QTEK6374

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture

Versatile, general purposed cleaner designed for use in production facilities.

#### 1.3 Details of the supplier of the safety data sheet Company

QTEK Manufacturing Limited,  
Unit 7  
Glenascaul Technology Park  
Oranmore,  
Galway,  
Ireland.  
Email: sales@qtek.com

#### 1.4 Emergency telephone number

Telephone Number: + (353) 91 745160

Fax Number: + (353) 91 751299

Hours of business (Monday to Friday):

0830 – 1730 hrs.

Closed Bank Holidays and Public Holidays

### 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2

H225: Highly flammable liquid and vapour.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness

# Isopropyl Alcohol

## 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : Prevention:

P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

## 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

Registration number: 01-2119457558-25-0000 (IPA)

Chemical Name	CAS-No. EINECS-No. / ELINCS No.	content [%]	classifications
propan-2-ol; isopropyl alcohol; isopropanol	67-63-0 200-661-7	100%	H225, H316, H336

See section 16 'Other Information' for full text of H Statements

# Isopropyl Alcohol

## 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice:	Take off contaminated clothing and shoes immediately.
If inhaled:	Move to fresh air.
In case of skin contact:	Wash off with plenty of water.
In case of eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
If swallowed:	Drink plenty of water. Do NOT induce vomiting. Obtain medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks:	No information available.
--------	---------------------------

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment:	For specialist advice physicians should contact the Poisons Information Service.
------------	--

## 5: FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing:	Water spray Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry powder
Unsuitable extinguishing media:	High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting :	No information available.
---	---------------------------

### 5.3 Advice for firefighters

Further information:	Use water spray to cool unopened containers.
----------------------	--

## 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :	Ensure adequate ventilation.
Keep away from sources of ignition - No smoking.	

### 6.2 Environmental precautions

Environmental precautions:	Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.
----------------------------	--

# Isopropyl Alcohol

## 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

## 6.4 Reference to other sections

For personal protection see section 8.

## 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Advice on safe handling : Ensure adequate ventilation.  
Vapours are heavier than air and may spread along floors.

Advice on protection against:  
fire and explosion : Keep away from sources of ignition - No smoking.  
Vapours may form explosive mixtures with air.  
Do not allow to enter drains (danger of explosion).  
Take precautionary measures against static discharges.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed.  
areas and containers : Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.  
German storage class: 3 Flammable Liquids

### 7.3 Specific end uses

: Consult the technical guidelines for the use of this substance/mixture.

## 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Isopropanol	67-63-0	TWA	200 ppm	2007	IR_OEL
		STEL	400 ppm	2007	IR_OEL
		TWA (15 mins)	500 ppm - 1250 mg/m <sup>3</sup>		WEL-UK
		TWS (8 hrs)	400 ppm - 999 mg/m <sup>3</sup>		WEL-UK
		Odour threshold	100 ppm - 245 mg/m <sup>3</sup>		

#### Occupational

DNEL : End Use: Workers  
propan-2-ol; isopropyl : Exposure routes: Skin contact  
alcohol; isopropanol : Potential health effects: Chronic effects  
Exposure time: 1 d  
Value: 888 mg/kg

# Isopropyl Alcohol

---

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Chronic effects  
Value: 500 mg/m<sup>3</sup>

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Chronic effects  
Exposure time: 1 d  
Value: 319 mg/kg

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Chronic effects  
Value: 89 mg/m<sup>3</sup>

End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Chronic effects  
Exposure time: 1 d  
Value: 26 mg/kg

PNEC  
propan-2-ol; isopropyl  
alcohol; isopropanol

:

Fresh water  
Value: 140,9 mg/l

Marine water  
Value: 140,9 mg/l

Fresh water sediment  
Value: 552 mg/kg

Marine sediment  
Value: 552 mg/kg

Soil  
Value: 28 mg/kg

## Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally required. In inadequately ventilated areas, where workplace limits are exceeded, where unpleasant odours exist or where aerosols are in use, or smoke and mist occur, use self-contained breathing apparatus or breathing apparatus with a type A filter or appropriate combined filter (e.g. where aerosols are in use, or smoke and mist occur, A-P2 or ABEK-P2), in compliance with EN 141.

# Isopropyl Alcohol

Eye protection:	Tightly fitting safety goggles (EN166, EN170 2-1.2)
Hand:	Normal length chemical-mechanical resistant gloves (EN374/EN388) Glove Material : butyl rubber Breakthrough time: >= 480 min Thickness: 0.5 mm
Hygiene measures:	Take off all contaminated clothing immediately.
Protective measures:	Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist.

## Environmental exposure controls

General advice :	Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.
------------------	--

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	:	Clear Liquid
Colour	:	colourless
Odour	:	alcohol-like
pH	:	not applicable
Melting point/range	:	-89 °C
Boiling point/boiling range	:	82 °C, 1.013 hPa
Flash point	:	12 °C
Lower explosion limit	:	2 %(V)
Upper explosion limit	:	12 %(V)
Vapour pressure	:	42 hPa, 20 °C
60,2 hPa, 25 °C	:	
Density	:	0,7855 g/cm <sup>3</sup> , 20 °C
Water solubility	:	completely miscible
Partition coefficient	:	noctanol/water
	:	log Pow: 0,05, 25 °C, (literature value)
Autoignition temperature	:	> 399 °C
Ignition temperature	:	425 °C
Thermal decomposition	:	No decomposition if used as directed.
Viscosity, dynamic	:	2,5 mPas, 20 °C
	:	2,1 mPas, 25 °C
Explosive properties	:	Not explosive

### 9.2 Other information

Oxidising potential	:	no data available
Refractive index	:	1,376 - 1,378, 20 °C

# Isopropyl Alcohol

## 10: STABILITY AND REACTIVITY

**10.1 Reactivity** no data available

**10.2 Chemical stability** no data available

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : no data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products : No decomposition if stored normally.

## 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Further information : no data available

#### **Components:**

#### **propan-2-ol; isopropyl alcohol; isopropanol :**

Acute oral toxicity : LD50: > 2.000 mg/kg, rat, GLP: no, (literature value)

Acute dermal toxicity : LD50: > 2.000 mg/kg, rabbit, GLP: no, (literature value)

Skin corrosion/irritation : rabbit, Result: not irritating, GLP: no, (literature value)

Serious eye damage/eye irritation : rabbit, Result: irritating, GLP: no, (literature value)

Respiratory or skin sensitization : Buehler Test, guinea pig, Result: not sensitizing, GLP

Germ cell mutagenicity

Genotoxicity in vitro without, Result : Ames test, Salmonella typhimurium, with and nor mutagenic, GLP: no, (literature value)

## 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### **Components:**

#### **propan-2-ol; isopropyl alcohol; isopropanol :**

Toxicity to fish : LC50: > 100 mg/l, 48 h, Leuciscus idus melanotus, static, GLP: no, (literature value)

Toxicity to daphnia and other aquatic invertebrates. EC50: > 100 mg/l, 48 h, Daphnia magna, static test, GLP: no, (literature value)

# Isopropyl Alcohol

Toxicity to algae : EC50: > 100 mg/l, 72 h, Scenedesmus subspicatus, static test, GLP: no, (literature value)

## 12.2 Persistence and degradability

### Components:

#### propan-2-ol; isopropyl alcohol; isopropanol :

Biodegradability : aerobic, > 70 %, Result: Readily biodegradable., Exposure time: 10 d, content: 7 mg/l, GLP: no, (literature value)

## 12.3 Bioaccumulative potential

## 12.4 Mobility in soil

## 12.5 Results of PBT and vPvB assessment

### Components:

#### propan-2-ol; isopropyl alcohol; isopropanol :

Assessment : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

## 12.6 Other adverse effects

### Product:

Additional ecological information : no data available

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

#### **Product :**

Following pre-treatment and observing the regulations for hazardous wastes, it must be taken to a permitted hazardous wastes landfill or hazardous wastes incinerator.

**Contaminated packaging :** Can be used after re-conditioning.

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number

ADR : 1219  
RID : 1219  
IMDG : 1219  
IATA : 1219

### 14.2 Proper shipping name

ADR : ISOPROPYL ALCOHOL, ISOPROPANOL  
RID : ISOPROPYL ALCOHOL, ISOPROPANOL  
IMDG : ISOPROPYL ALCOHOL, ISOPROPANOL  
IATA : ISOPROPANOL

# Isopropyl Alcohol

---

## 14.3 Transport hazard class

<b>ADR</b>	:	3
<b>RID</b>	:	3
<b>IMDG</b>	:	3
<b>IATA</b>	:	3

## 14.4 Packing group

### ADR

Packaging group	:	II
Classification Code	:	F1
Hazard identification No	:	33
Labels	:	3
Tunnel restriction code	:	(D/E)

### RID

Packaging group	:	II
Classification Code	:	F1
Hazard identification No	:	33
Labels	:	3

### IMDG

Packaging group	:	II
Labels	:	3
EmS Number	:	F-E, S-D

### IATA

Packing instruction (cargo aircraft)	:	307
Packaging group	:	II
Labels	:	3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous	:	no
---------------------------	---	----

### RID

Environmentally hazardous	:	no
---------------------------	---	----

### IMDG

Marine pollutant	:	no
------------------	---	----

### IATA

Environmentally hazardous	:	no
---------------------------	---	----

## 14.6 Special precautions for user

no data available

# Isopropyl Alcohol

## 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Z

## 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Major Accident Hazard : 96/82/EC  
Legislation : Highly flammable  
Quantity 1: 5.000 t  
Quantity 2: 50.000 t

#### Notification status

EINECS	On the inventory, or in compliance with the inventory
TSCA	On TSCA Inventory
AUSTR	On the inventory, or in compliance with the inventory
DSL	All components of this product are on the Canadian DSL list.
ENCS	On the inventory, or in compliance with the inventory
KOREA	On the inventory, or in compliance with the inventory
PHIL	On the inventory, or in compliance with the inventory
CHINA	On the inventory, or in compliance with the inventory
ISHL	On the inventory, or in compliance with the inventory
NZIOC	On the inventory, or in compliance with the inventory

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

# Isopropyl Alcohol

---

## Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The data contained herein is based on information currently available to QTEK Manufacturing Limited and is believed to be factual. As a blender, and compounder, QTEK Manufacturing Limited does not manufacture the raw materials used in this product and correspondingly relies on information provided to QTEK Manufacturing Limited from material safety data sheets on the specific raw materials in the construction of this material safety data sheet. Such information is, to the best of QTEK Manufacturing Limited knowledge and belief, accurate and reliable as of the date of this MSDS. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY, OR COMPLETENESS. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular application. This information is not intended to be all-inclusive as of the manner and conditions of use, handling and storage. Other factors may involve other or additional safety or performance considerations. This data is not to be taken as a warranty or representation of which QTEK Manufacturing Limited assumes legal responsibility.