BUSHMASTERTM LANDSCAPING UNIT - POLYCARBONATE VISOR

PRODUCT CODE: AFZ061-131-100

DESIGNED FOR MAXIMUM COMFORT AND OPTIMUM PROTECTION

TECHNICAL SPECIFICATION

HEARING PROTECTION

VISOR:

Polycarbonate

VISOR CARRIER: Polypropylene

HEADBAND:

PVC covered wire band

INSTRUCTIONS FOR USE

Before use the visor should be fitted onto a Bushmaster Browguard

In use ensure that the visor carrier and ear defenders fit comfortably and securely on the head

Ensure that the visor and ear defenders are in place before entering the hazard area

BUSHMASTER[™] FEATURES

Quick Release Detachable Visor: Allows ear defenders to be used on their own and the visor to be changed easily

Quick Release Visor Fixings: Allows quick and easy replacement of Polycarbonate or Wire Mesh Visor

Flip-Up Locking Hinge: Allows the visor to be safely flipped up and locked at a 90° angle for closer inspection of work in between or after work sessions

Padded Headband and Earcaps: Added comfort for prolonged use





The unit may be cleaned with soap and warm water and dried with a soft cloth

The unit should not be cleaned with chemical or abrasive cleaners

The unit should be stored out of direct sunlight

WWWJSPCO.UK

The unit should be stored away from chemicals and extremes of temperature



CONFORMITY

Ear Defender conforms to EN 352:2002, SNR of 30 Visor conforms to EN 166:2001.B Placed on CE Certificate Number 525924, issued by BSi



MANUFACTURING FOR SAFETY





BUSHMASTER[™]

PRODUCT CODE: AFZ061-131-100

DESIGNED FOR MAXIMUM COMFORT AND OPTIMUM PROTECTION

TECHNICAL SPECIFICATION

HEARING PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

(JSP)

BUSHMAS

Weight: 485g (Approx.)



HEIGHT: 245mm

LANDSCAPING UNIT - POLYCARBONATE VISOR

DIMENSIONS OF BUSHMASTER™

WIDTH:

225mn

Height: 249mm
Width: 230mm
Length: 245mm
Weight of Ear Defenders: 0.23Kg (Approx.)
Ear Defender Cup Open Area: 40mm x 65mm
Weight of Polycarbonate Visor: 0.12kg (Approx.)





BUSHMASTER[™] PERFORMANCE

Offers general robustness protection against particles at 12m/s Ear defenders offer an SNR of 30

Designed for maximum comfort and optimum protection for users where head protection (safety helmets) is not mandatory

The Bushmaster combines the high protection factor ear defenders, JSP Classic Extreme, with a choice of interchangeable visors depending on the application

LIMITATIONS OF USE

Protection will only be offered if the unit is fitted correctly Ear pads may deteriorate with use and should be examined at frequent intervals

If the visor becomes scratched or damaged it should be replaced

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer

The unit when in contact with the skin may cause allergic reactions to susceptible individuals

If this occurs leave the hazard area, remove the faceshield and seek medical advice

If the ear defender is to be worn for long periods the noise level must be reduced to 80dB

Before selection of a suitable ear defender a noise survey should be carried out

Spectacle frames and hair between the ear pads and the head may affect the performance of the ear defender

Hearing Protection should be used in accordance with the European Physical Agents (Noise) Directive 2003/10/EC

The Polycarbonate visor is not suitable for use with all chemicals - if you are unsure contact your supplier or JSP for advice



MANUFACTURING FOR SAFETY WWWJSPCO.UK

