

by Honeywell

Technical specifications

BANDIT TOOL LANYARD

Tools are attached with the karabiner or by cinching the cord around tool. It prevents injuries, reduce tool loss and increase worker productivity while working at heights. Lanyard conveniently attaches to the user's belt.

Reference :

- 1100210 for box of 12 units bandit tool lanyard
- 1013200 for 1 each bandit tool lanyard
- 1012490 for box of 36 units bandit tool lanyard
- 1012491 for box of 36 units Wrist bandit tool lanyard
- 1014592 for 1 each Wrist bandit tool lanyard
- 1014591 for 1 each bandit tool lanyard

Features

- Constructed of nylon tubular webbing with an attached nylon cord and karabiner
- Lightweight karabiner can be used to attach to belt or belt loops, or to attach tools.
- Integral loop can be used to cinch around a belt or loops.





<u>Maximum weight of the tool : 2,5 Kgs</u> Minimum length of the tool lanyard without karabiner = 66 cmMaximum length of the tool lanyard without karabiner = 112 cm

> SPERIAN FALL PROTECTION FRANCE SAS 35-37 rue de la Bidauderie F - 18100 Vierzon - France Tel : +33 2 48 52 40 40 Fax : +33 2 48 71 04 97 Web site : www.honeywellsafety.com

